

Our **Office Tower OP Series UPS Systems** are a landmark in the tradition of excellence our engineering team has achieved. They sacrifice neither features nor power, and mark the right choice for a **SOHO** and **mid-Business Application** environments. They are designed for customers who value versatility, manageability and performance on a stable platform .

These series have been developed on a **Line-Interactive** hardware platform. With a number of battery & surge backed outlets, enhanced safety features and a highly controlled operation, you can go ahead and connect onto them your most vital computer systems and related peripherals, being ready in case of a power outage!

Unique features within these models make them easy to use and manage, protecting your investment for many years to come! From functionality down to aesthetic details, our **Office Tower OP Series** mark a good recommendation for your backup power needs.



MODELS: OP 550E & 750E



MODELS: OP 1000UE & 1500UE

- Line Interactive Technology
- Hot Swappable Batteries
- Microprocessor based full Digital Control
- Automatic Voltage Regulator
- PC Connectivity/Control Solution
- EMI, RFI, Surge & Lighting Spike Protection
- Phone, Fax, Modem, DSL, and Network Protection
- Elaborate Power Management Software Included
- Programmable Brownout and Over-Voltage Protection
- We offer 25,000.- EUR Connected Equipment Life Time Guarantee
- Auto-Restart, Auto-Charge, and Scheduled Shutdown Function
- High Performance Output
- Elaborate Features and High Reliability suitable for SOHO and middle size Business Environments



PowerPanel® Plus Management Software



AUTO-SHUTDOWN SOFTWARE
CyberPower PowerPanel® Plus Management Software, is Compatible with Windows XP, 2000 Professional, ME, 98, Server 2003, & Linux.

CAPACITY & RUN-TIME:

- **OP 550E:** 550VA or 330W. **OP 750E:** 750VA or 450W. **OP 1000UE:** 1000VA or 700W. **OP 1500UTE:** 1500VA or 900W
- TYPICAL RUNTIME: **OP 550E:** 20 min. **OP 750E:** 36 min. **OP 1000UE:** 60 min. **OP 1500UTE:** 72 min

INPUT POWER:

- Voltage Range: 185V ~ 270V
- Frequency Range: 50Hz / 60 Hz (+/- 3Hz) auto-sensing

OUTPUT POWER:

- On Battery Output Voltage: Simulated Sine-Wave at 230V (+/- 5%)
- On Battery Output Frequency: 50Hz / 60 Hz (+/- 1%)
- Typical Transfer Time: 4ms
- Overload Protection Scheme: *On Main Power by Fuse*, and on Battery Power by *Internal Current Limiting*
- Automatic Voltage Regulator (AVR): Boost / Buck

BATTERY INFORMATION:

- Sealed Maintenance-Free Lead-Acid Batteries, Hot Swappable, and Replaceable by User
- **OP 550E:** 12V, 7 AH x 1. **OP 750E:** 12V, 9 AH x 1. **OP 1000UE:** 12V, 7.2 AH x 2. **OP 1500UTE:** 12V, 9 AH x 2
- Typical Recharge Time: 8 Hours

STATUS INDICATORS:

- Power-On LED
- Using Battery LED
- Boost LED
- Buck LED
- Audio Alarms for: Overload, On-Battery, and Low-Battery

RECEPTACLES:

- **OP 1000UE & 1500UTE:** Six IEC 320 C13 Plugs (4 for Battery Backup & Surge & 2 only for Surge Protection)
- **OP 550E & 750E:** Four IEC 320 C13 Plugs (3 for Battery Backup & Surge & 1 only for Surge Protection)
- RJ11/RJ45 Input/Output for Surge Protection

CONNECTORS:

- **OP 1000UE & 1500UTE:** USB and RS-232 Serial Connectors to PC or Server
- **OP 550E & 750E:** RS-232 Serial Connector to PC or Server

MANAGEMENT & CONTROL:

- Manual Self-Test
- Auto Re-Charge
- Auto Re-Start
- Scheduled Shutdown Function
- Programmable Brownout and Over-Voltage Protection
- Power Panel[®] Plus elaborate software for PC connectivity and Management Control

PHYSICAL INFORMATION:

Dimensions (mm): **OP 1000UE & 1500UTE:** 309 (L) x 141 (W) x 184 (H). **OP 550E & 750E:** 283 (L) x 91 (W) x 164 (H)
Weight: **OP 550E:** 6.5kg. **OP 750E:** 7.6kg. **OP 1000UE:** 12.3kg. **OP 1500UTE:** 14.2kg
Storage Temperature: -15°C ~ +45°C
Operating Temperature: 0°C ~ 35°C
Operating Humidity: 0%~95% non-condensed



DISTRIBUTED BY:

CyberPower's
Manufacturing
Facilities are
ISO 9001:2000,
ISO 14000, and
QC080000
Approved